




Reducing Flexible Coupling (MODEL XGQT3)

Nominal Size mm/in	Pipe O.D mm/in	Working pressure (Mpa)	Dimensions			Bolt/Nut No.-size (mm)
			ΦD	L	H	
			mm	mm	mm	
40×32	48.3×42.4		72	108	46	
1½×1¼	1.9×1.669					
50×40	60.3×48.3		89.6	132	46	
2×1½	2.375×1.9					
65×50	73×60.3		101	147	46	2-⅜×55 (2-M10×55)
2½×2	2.875×2.375					
65×50	76.1×60.3		101	147	46	
2½×2	3×2.375					
80×50	88.9×60.3		121.6	168	46	
3×2	3.5×2.375					
80×65	88.9×73.0		121.6	168	46	
3×2½	3.5×2.875					
80×65	88.9×76.1		121.6	168	46	
3×2½	3.5×3					
100×50	114.3×60.3		149.2	200	50	2-½×75 (2-M12×75)
4×2	4.5×2.375					
100×65	114.3×73.0		149.2	200	50	
4×2½	4.5×2.875					
100×65	114.3×76.1	2.5MPa (300PSI)	149.2	200	50	
4×2½	4.5×3.0					
100×80	114.3×88.9		149.2	200	50	
4×3	4.5×3.5					
125×100	139.7×114.3		156	235	50	
5×4	5.5×4.5					
150×80	165.1×88.9		207	273	50	
6×3	6.5×3.5					
150×100	165.1×114.3		207	273	50	2-⅝×85 (2-M16×85)
6×4	6.5×4.5					
150×80	168.3×88.9		209.4	272	50	
6×3	6.525×3.5					
150×100	168.3×114.3		209.4	272	50	
6×4	6.525×4.5					
200×150	219.1×165.1		276	347	58	2-¾×90 (2-M20×90)
8×6	8.625×6.5					
200×150	219.1×168.3		276	347	58	
8×6	8.625×6.525					