




CHRYSSAFIDIS

ΔΙΑΚΛΑΔΩΣΕΙΣ ΜΕ ΣΠΕΙΡΩΜΑ BSP



Threaded Mechanical Tee (MODEL XGQT04)



Nominal Size mm/in	Pipe O.D mm/in	Working pressure (Mpa)	Dimensions			Bolt/Nut No.-size (mm)	Hole Dimension (mm)+1	
			A	L	H			
			mm	mm	mm			
50 x 15	60.3 x Rc ¹ / ₂	1.6MPa (230PSI)	110	59	50	2- ¹ / ₂ x 40 (2-M10 x 40)	φ 30	
2 x ¹ / ₂	2.375 x 0.825							
50 x 20	60.3 x Rc ³ / ₄		112	59	50		φ 30	
2 x ³ / ₄	2.375 x 1.05							
50 x 25	60.3 x Rc1		120	72	50		φ 38	
2 x 1	2.375 x 1.327							
50 x 32	60.3 x Rc1 ¹ / ₄		120	83	55			φ 46
2 x 1 ¹ / ₄	2.375 x 1.669							
50 x 40	60.3 x Rc1 ¹ / ₂		120	83	63			φ 46
2 x 1 ¹ / ₂	2.375 x 1.9							
65 x 15	76.1 x Rc ¹ / ₂		139	62	58		2- ³ / ₈ x 55 (2-M10 x 55)	φ 30
2 ¹ / ₂ x ¹ / ₂	3 x 0.825							
65 x 20	76.1 x Rc ³ / ₄		139	62	63			φ 30
2 ¹ / ₂ x ³ / ₄	3 x 1.05							
65 x 25	76.1 x Rc1		139	76	60			φ 38
2 ¹ / ₂ x 1	3 x 1.327							
65 x 32	76.1 x Rc1 ¹ / ₄		138	83	60			φ 46
2 ¹ / ₂ x 1 ¹ / ₄	3 x 1.669							
65 x 40	76.1 x Rc1 ¹ / ₂		139	90	60			φ 53
2 ¹ / ₂ x 1 ¹ / ₂	3 x 1.9							
80 x 15	88.9 x Rc ¹ / ₂		155	59	70	φ 30		
3 x ¹ / ₂	3.5 x 0.825							
80 x 20	88.9 x Rc ³ / ₄		155	59	70	φ 30		
3 x ³ / ₄	3.5 x 1.05							
80 x 25	88.9 x Rc1		152	76	63.5	φ 38		
3 x 1	3.5 x 1.327							
80 x 32	88.9 x Rc1 ¹ / ₄		152	83	64.5	φ 46		
3 x 1 ¹ / ₄	3.5 x 1.669							
80 x 40	88.9 x Rc1 ¹ / ₂		152	90	65.5	φ 53		
3 x 1 ¹ / ₂	3.5 x 1.9							
80 x 50	88.9 x Rc2		152	98	66.5	φ 64		
3 x 2	3.5 x 2.375							
100 x 25	108.1 x Rc1		167	76	76	φ 38		
4 x 1	4.250 x 1.327							
100 x 32	108.0 x Rc1 ¹ / ₄		167	83	76	φ 46		
4 x 1 ¹ / ₄	4.25 x 1.669							
100 x 40	108.0 x Rc1 ¹ / ₂		167	90	76	φ 53		
4 x 1 ¹ / ₂	4.25 x 1.9							
100 x 50	108.0 x Rc2		167	100	78	φ 64		
4 x 2	4.25 x 2.375							
100 x 65	108.0 x Rc2 ¹ / ₂		167	117	79	φ 80		
4 x 2 ¹ / ₂	4.25 x 3							
100 x 80	108 x Rc3		167	129	82	2- ¹ / ₂ x 65 (2-M12 x 65)	φ 92	
4 x 3	4.25 x 3.5							
100 x 25	114.3 x Rc1		181	76	79	φ 38		
4 x 1	4.5 x 1.327							
100 x 32	114.3 x Rc1 ¹ / ₄		181	83	79	φ 46		
4 x 1 ¹ / ₄	4.5 x 1.669							
100 x 40	114.3 x Rc1 ¹ / ₂		181	90	79	φ 53		
4 x 1 ¹ / ₂	4.5 x 1.9							
100 x 50	114.3 x Rc2		181	100	79	φ 64		
4 x 2	4.5 x 2.375							
100 x 65	114.3 x Rc2 ¹ / ₂		181	117	81	φ 80		
4 x 2 ¹ / ₂	4.5 x 3							
100 x 80	114.3 x Rc3		181	129	82	φ 92		
4 x 3	4.5 x 3.5							




螺纹式机械三通(型号XGQT04) Threaded Mechanical Tee (MODEL XGQT04)



Nominal Size mm/in	Pipe O.D mm/in	Working pressure (Mpa)	Dimensions			Bolt/Nut No.-size (mm)	Hole Dimension (mm)+1
			尺寸				
			规格	管子基本尺寸	工作压力	A mm	L mm
125×25	133.0×Rc1	1.6MPa (230PSI)	205	76	89	2-1/2×75 (2-M12×75)	φ38
5×1	5.250×1.327						
125×32	133.0×Rc1 1/4		205	82	89		φ46
5×1 1/4	5.25×1.669						
125×40	133.0×Rc1 1/2		205	90	89		φ53
5×1 1/2	5.25×1.9						
125×50	133.0×Rc2		205	100	89		φ64
5×2	5.25×2.375						
125×65	133.0×Rc2 1/2		205	117	92		φ80
5×2 1/2	5.25×3						
125×80	133.0×Rc3		205	129	94		φ92
5×3	5.25×3.5						
125×25	139.7×Rc1	1.6MPa (230PSI)	212	76	93	2-1/2×75 (2-M12×75)	φ38
5×1	5.5×1.327						
125×32	139.7×Rc1 1/4		212	83	93		φ46
5×1 1/4	5.5×1.669						
125×40	139.7×Rc1 1/2		212	90	93		φ53
5×1 1/2	5.5×1.9						
125×50	139.7×Rc2		212	100	93		φ64
5×2	5.5×2.375						
125×65	139.7×Rc2 1/2		212	117	93		φ80
5×2 1/2	5.5×3						
125×80	139.7×Rc3		212	129	95		φ92
5×3	5.5×3.5						
125×25	141.3×Rc1	1.6MPa (230PSI)	212	76	93	2-1/2×75 (2-M12×75)	φ38
5×1	5.563×1.327						
125×32	141.3×Rc1 1/4		212	83	93		φ46
5×1 1/4	5.563×1.669						
125×40	141.3×Rc1 1/2		212	90	93		φ53
5×1 1/2	5.563×1.9						
125×50	141.3×Rc2		212	100	93		φ64
5×2	5.563×2.375						
125×65	141.3×Rc2 1/2		212	117	93		φ80
5×2 1/2	5.563×3						
125×80	141.3×Rc3		212	129	95		φ92
5×3	5.563×3.5						
150×25	159×Rc1	1.6MPa (230PSI)	233	76	101.5	2-3/4×75 (2-M14×75)	φ38
6×1	6.250×1.327						
150×32	159.0×Rc1 1/4		233	83	101.5		φ46
6×1 1/4	6.250×1.669						
150×40	159.0×Rc1 1/2		233	90	101.5		φ53
6×1 1/2	6.250×1.9						
150×50	159.0×Rc2		233	100	101.5		φ64
6×2	6.250×2.375						
150×65	159.0×Rc2 1/2		233	117	105.5		φ80
6×2 1/2	6.250×3						
150×80	159.0×Rc3		233	129	105.5		φ92
6×3	6.250×3.5						
150×100	159.0×Rc4	1.6MPa (230PSI)	233	157	110	2-3/4×75 (2-M14×75)	φ118
6×4	6.250×4.5						
150×25	165.1×Rc1		239	76	106		φ38
6×1	6.5×1.327						
150×32	165.1×Rc1 1/4		239	83	106		φ46
6×1 1/4	6.5×1.669						
150×40	165.1×Rc1 1/2	1.6MPa (230PSI)	239	90	106	2-3/4×75 (2-M14×75)	φ53
6×1 1/2	6.5×1.9						



螺纹式机械三通(型号XGQT04) Threaded Mechanical Tee (MODEL XGQT04)



Nominal Size mm/in	Pipe O.D mm/in	Working pressure (Mpa)	Dimensions			Bolt/Nut No.-size (mm)	Hole Dimension (mm)
			尺寸				
规格	管子基本尺寸	工作压力	A mm	L mm	H mm	螺栓	开孔尺寸
150 × 50	165.1 × Rc2		239	100	106		φ 64
6 × 2	6.5 × 2.375						
150 × 65	165.1 × Rc2 1/2		239	117	106		φ 80
6 × 2 1/2	6.5 × 3						
150 × 80	165.1 × Rc3		239	129	108		φ 92
6 × 3	6.5 × 3.5						
150 × 100	165.1 × Rc4		239	157	110		φ 118
6 × 4	6.5 × 4.5						
150 × 25	168.3 × Rc1		239	76	106		φ 38
6 × 1	6.625 × 1.327						
150 × 32	168.3 × Rc1 1/4		239	83	106	2-9/16 × 75 (2-M14 × 75)	φ 46
6 × 1 1/4	6.625 × 1.669						
150 × 40	168.3 × Rc1 1/2		239	90	106		φ 53
6 × 1 1/2	6.625 × 1.9						
150 × 50	168.3 × Rc2		239	100	106		φ 64
6 × 2	6.625 × 2.375						
150 × 65	168.3 × Rc2 1/2		239	117	106		φ 80
6 × 2 1/2	6.625 × 3						
150 × 80	168.3 × Rc3		239	129	108		φ 92
6 × 3	6.625 × 3.5						
150 × 100	168.3 × Rc4		239	157	110		φ 118
6 × 4	6.625 × 4.5						
200 × 25	219.1 × Rc1		311	76	131		φ 38
8 × 1	8.625 × 1.327						
200 × 32	219.1 × Rc1 1/4		311	83	134		φ 46
8 × 1 1/4	8.625 × 1.669						
200 × 40	219.1 × Rc1 1/2		311	90	134		φ 53
8 × 1 1/2	8.625 × 1.9						
200 × 50	219.1 × Rc2		311	100	134	2-9/16 × 85 (2-M16 × 85)	φ 64
8 × 2	8.625 × 2.375						
200 × 65	219.1 × Rc2 1/2		311	117	134		φ 80
8 × 2 1/2	8.625 × 3						
200 × 80	219.1 × Rc3		311	129	134		φ 92
8 × 3	8.625 × 3.5						
200 × 100	219.1 × Rc4		311	157	134		φ 118
8 × 4	8.625 × 4.5						