




**ΣΠΡΙΝΚΛΕΡ**

UPRIGHT SPRINKLER with water paraboloid distribution, suitable for supplying the water needed when the jet is set upwards against the washer. The acronym of the sprinkler "SU" and the operating temperature of the glass bulb are indicated on the washer.

89/106/CEE (CPD) - UNI EN 12259-1



299221


G5

STANDARD  
RESPONSE

| Art.          | Model   | K Factor | Connection | Temperature     | Price |
|---------------|---------|----------|------------|-----------------|-------|
| 63.2.090.0250 | Upright | 80       | 1/2"       | 57 °C = 135 °F  | 5,36  |
| 63.2.090.0251 | Upright | 80       | 1/2"       | 68 °C = 155 °F  | 5,36  |
| 63.2.090.0252 | Upright | 80       | 1/2"       | 79 °C = 175 °F  | 5,36  |
| 63.2.090.0253 | Upright | 80       | 1/2"       | 93 °C = 200 °F  | 5,36  |
| 63.2.090.0254 | Upright | 80       | 1/2"       | 141 °C = 286 °F | 5,73  |
| 63.2.090.0255 | Upright | 80       | 1/2"       | 182 °C = 360 °F | 5,73  |

UPRIGHT SPRINKLER with water paraboloid distribution, suitable for supplying the water needed when the jet is set upwards against the washer. The acronym of the sprinkler "SU" and the operating temperature of the glass bulb are indicated on the washer.

89/106/CEE (CPD) - UNI EN 12259-1




F3

QUICK  
RESPONSE

| Art.          | Model   | K Factor | Connection | Temperature     | Price |
|---------------|---------|----------|------------|-----------------|-------|
| 63.2.090.0220 | Upright | 80       | 1/2"       | 57 °C = 135 °F  | 7,34  |
| 63.2.090.0221 | Upright | 80       | 1/2"       | 68 °C = 155 °F  | 7,34  |
| 63.2.090.0222 | Upright | 80       | 1/2"       | 79 °C = 175 °F  | 7,34  |
| 63.2.090.0223 | Upright | 80       | 1/2"       | 93 °C = 200 °F  | 7,34  |
| 63.2.090.0224 | Upright | 80       | 1/2"       | 141 °C = 286 °F | 7,73  |

CHROME UPRIGHT SPRINKLER with water paraboloid distribution, suitable for supplying the water needed when the jet is set upwards against the washer. The acronym of the sprinkler "SU" and the operating temperature of the glass bulb are indicated on the washer.

89/106/CEE (CPD) - UNI EN 12259-1




G5

STANDARD  
RESPONSE

| Art.          | Model   | K Factor | Connection | Temperature     | Price |
|---------------|---------|----------|------------|-----------------|-------|
| 63.C.090.0250 | Upright | 80       | 1/2"       | 57 °C = 135 °F  | 5,76  |
| 63.C.090.0251 | Upright | 80       | 1/2"       | 68 °C = 155 °F  | 5,76  |
| 63.C.090.0252 | Upright | 80       | 1/2"       | 79 °C = 175 °F  | 5,76  |
| 63.C.090.0253 | Upright | 80       | 1/2"       | 93 °C = 200 °F  | 5,76  |
| 63.C.090.0254 | Upright | 80       | 1/2"       | 141 °C = 286 °F | 6,16  |
| 63.C.090.0255 | Upright | 80       | 1/2"       | 182 °C = 360 °F | 6,16  |

CHROME UPRIGHT SPRINKLER with water paraboloid distribution, suitable for supplying the water needed when the jet is set upwards against the washer. The acronym of the sprinkler "SU" and the operating temperature of the glass bulb are indicated on the washer.

89/106/CEE (CPD) - UNI EN 12259-1



F3

QUICK  
RESPONSE

| Art.          | Model   | K Factor | Connection | Temperature     | Price |
|---------------|---------|----------|------------|-----------------|-------|
| 63.C.090.0220 | Upright | 80       | 1/2"       | 57 °C = 135 °F  | 7,73  |
| 63.C.090.0221 | Upright | 80       | 1/2"       | 68 °C = 155 °F  | 7,73  |
| 63.C.090.0222 | Upright | 80       | 1/2"       | 79 °C = 175 °F  | 7,73  |
| 63.C.090.0223 | Upright | 80       | 1/2"       | 93 °C = 200 °F  | 7,73  |
| 63.C.090.0224 | Upright | 80       | 1/2"       | 141 °C = 286 °F | 8,14  |



Από το



1882

SPRINKLER

CPF  
FIRE

2992xxA 2/2

ΧΡΥΣΑΦΙΑΗΣ Α.Ε.

PENDENT SPRINKLER with water paraboloid distribution, suitable for supplying the water needed when the jet is set downwards against the washer. The acronym of the sprinkler "SP" and the operating temperature of the glass bulb are indicated on the washer.

89/106/CEE (CPD) - UNI EN 12259-1

| Art.          | Model   | K Factor | Connection |                 | € Price |
|---------------|---------|----------|------------|-----------------|---------|
| 63.2.090.0240 | Pendent | 80       | 1/2"       | 57 °C = 135 °F  | 5,56    |
| 63.2.090.0241 | Pendent | 80       | 1/2"       | 68 °C = 155 °F  | 5,56    |
| 63.2.090.0242 | Pendent | 80       | 1/2"       | 79 °C = 175 °F  | 5,56    |
| 63.2.090.0243 | Pendent | 80       | 1/2"       | 93 °C = 200 °F  | 5,56    |
| 63.2.090.0244 | Pendent | 80       | 1/2"       | 141 °C = 286 °F | 5,96    |
| 63.2.090.0245 | Pendent | 80       | 1/2"       | 182 °C = 360 °F | 5,96    |

299201



G5

STANDARD  
RESPONSE

PENDENT SPRINKLER with water paraboloid distribution, suitable for supplying the water needed when the jet is set downwards against the washer. The acronym of the sprinkler "SP" and the operating temperature of the glass bulb are indicated on the washer.

89/106/CEE (CPD) - UNI EN 12259-1

| Art.          | Model   | K Factor | Connection |                 | € Price |
|---------------|---------|----------|------------|-----------------|---------|
| 63.2.090.0210 | Pendent | 80       | 1/2"       | 57 °C = 135 °F  | 7,55    |
| 63.2.090.0211 | Pendent | 80       | 1/2"       | 68 °C = 155 °F  | 7,55    |
| 63.2.090.0212 | Pendent | 80       | 1/2"       | 79 °C = 175 °F  | 7,55    |
| 63.2.090.0213 | Pendent | 80       | 1/2"       | 93 °C = 200 °F  | 7,55    |
| 63.2.090.0214 | Pendent | 80       | 1/2"       | 141 °C = 286 °F | 7,95    |



F3

QUICK  
RESPONSE

CHROME PENDENT SPRINKLER with water paraboloid distribution, suitable for supplying the water needed when the jet is set downwards against the washer. The acronym of the sprinkler "SP" and the operating temperature of the glass bulb are indicated on the washer.

89/106/CEE (CPD) - UNI EN 12259-1

| Art.          | Model   | K Factor | Connection |                 | € Price |
|---------------|---------|----------|------------|-----------------|---------|
| 63.C.090.0240 | Pendent | 80       | 1/2"       | 57 °C = 135 °F  | 5,96    |
| 63.C.090.0241 | Pendent | 80       | 1/2"       | 68 °C = 155 °F  | 5,96    |
| 63.C.090.0242 | Pendent | 80       | 1/2"       | 79 °C = 175 °F  | 5,96    |
| 63.C.090.0243 | Pendent | 80       | 1/2"       | 93 °C = 200 °F  | 5,96    |
| 63.C.090.0244 | Pendent | 80       | 1/2"       | 141 °C = 286 °F | 6,36    |
| 63.C.090.0245 | Pendent | 80       | 1/2"       | 182 °C = 360 °F | 6,36    |

299214



G5

STANDARD  
RESPONSE

CHROME PENDENT SPRINKLER with water paraboloid distribution, suitable for supplying the water needed when the jet is set downwards against the washer. The acronym of the sprinkler "SP" and the operating temperature of the glass bulb are indicated on the washer.

89/106/CEE (CPD) - UNI EN 12259-1

| Art.          | Model   | K Factor | Connection |                 | € Price |
|---------------|---------|----------|------------|-----------------|---------|
| 63.C.090.0210 | Pendent | 80       | 1/2"       | 57 °C = 135 °F  | 7,95    |
| 63.C.090.0211 | Pendent | 80       | 1/2"       | 68 °C = 155 °F  | 7,95    |
| 63.C.090.0212 | Pendent | 80       | 1/2"       | 79 °C = 175 °F  | 7,95    |
| 63.C.090.0213 | Pendent | 80       | 1/2"       | 93 °C = 200 °F  | 7,95    |
| 63.C.090.0214 | Pendent | 80       | 1/2"       | 141 °C = 286 °F | 8,35    |



F3

QUICK  
RESPONSE